

Transparent Display

Transparent OLED 55"

MIRAGE **NEW**



The **MIRAGE** Series is a brand-new type of transparent Screen, which makes it possible to achieve transparency even without a backlight. The Transparent OLED consists of self-emitting diodes which can operate in any environment. Without the need of a backlight or showcase, the **MIRAGE see-through OLED screen** can be placed in the middle of a room or integrated into a wall - the functionality is still given!



| | |
|-----------------|--|
| MIR55L | MIRAGE Transparent OLED 55" |
| MIR55FFL | MIRAGE Transparent MultiTouch OLED 55" |
| MIR55SL | MIRAGE Transparent OLED Stele 55" |
| MIR55FFL | MIRAGE Transparent MultiTouch OLED Stele 55" |

TOUCH

NON-TOUCH

TOUCH

NON-TOUCH



SINGLE DISPLAY

ALL-IN-ONE STELE



MMT GmbH & Co. KG - Waldenserstr. 2-4, 10551 Berlin, Germany
Phone: +49 (0) 30 39886850 - Web: www.mmt.io - Email: sales@mmt.io

55"

MIRAGE 55"

| | |
|--------------------------------------|---|
| Display diagonal | 1388 mm (55") |
| Resolution | 1920x1080 px @ 120 Hz |
| Transparency | 45% |
| Panel | AMOLED (Active Matrix Organic Light-Emitting Diode) |
| Active Display Area | 1209.6 x 680.4 mm |
| Brightness Fullscreen | 150 cd/m2 (typical), 165 cd/m2 (maximum, center of the screen) |
| Brightness Peak 1% | 500 cd/m2 (typical), 550 cd/m2 (maximum, center of the screen) |
| Aspect Ratio | 16:9 |
| Contrast | 100.000:1 |
| Viewing Angle | 178° H/V |
| Colors | 1.07Billion, 10bit |
| Response Time | 1 ms |
| Color Gamut | 100% of NTSC |
| Pixels Per Inch / Pixel Pitch | PPI 40, 0.63mm |
| Connections | 4x HDMI, 1x DisplayPort |
| Controls | Keypad, IR Remote Control |
| Orientation | Landscape & Portrait |
| Power Consumption | TOUCH: 165W (205W max.) NON-TOUCH: 140W (180W max.) |
| Operation Time | 8h / day, 7d / week (Attention: Content Guide) |
| Operating Conditions | Storage -20°C to 65°C / Working 0°C to 40°C |
| Dimensions (mm) | MIR55L: 1221.4 x 950 mm MIR55FFL: 1300 x 1000 mm MIRS55L: 1350 x 1960 mm MIRS55FFL: 1350 x 2000 mm |
| Border Width (mm) | TOUCH: 45/45/45/310.7 mm NON-TOUCH: 5/5/5/260.7 mm |
| Weight | MIR55L: tba. MIR55FFL: tba. MIRS55L: tba. MIRS55FFL: tba. |

| | |
|-----------------------------|---|
| Safety Glass | 3.2mm Safety Glass |
| Delivered Contents | Power Cord, USB Cable (Touch), IR Remote Control, Batteries |
| Lifetime | 30.000h (dynamic image at 25°C) (Attention: Content Guide) |
| Warranty | 18 Months Parts & Labor |
| Touch Technology | InGlass™ Touch Technology |
| Touch Points | 40 independent Touch Points |
| Touch Accuracy | <2 mm |
| Touch Response Time | <15 ms |
| Touch Reporting Rate | 100 Hz |
| Touch Method | Fingers, gloves, soft tip styluses and soft objects - min. size 4mm |
| Touch Interface | USB |
| Supported OS | Windows 10 / Windows 8 / Windows 7 / Android / Linux |